

## Pipe Hangers

Pipe hangers are used to support a sprinkler piping system from the building structure. Two or more listed components may be required to form a complete hanger assembly. The specific components required depend upon the type of building construction and the pipe size.

## C-Type Clamps

A type of clamp that is used to provide a load carrying connection to the flange of a building structural element, usually by use of a jaw and setscrew combination. It also provides for the attachment of a threaded rod.

### Sikla GmbH, C- Type Clamps

<i>Product Designation</i>	<i>Hanger Rod Size, mm</i>	<i>Component Description</i>	<i>For Nominal Pipe Sizes, in.</i>	<i>Remarks</i>
TCS-0	10	Beam Clamp	3/4 through 4	-
TCS-I	10	Beam Clamp	3/4 through 4	-
TCS-II	12, 16	Beam Clamp	5 through 8	-
TCS OLC	10	Beam Clamp	3/4 through 4	-
TCS F	10	Beam Clamp	3/4 through 4	a

**Remarks:**

a. Approved for M10 hanger rod only

<b>Company Name:</b>	Sikla GmbH & Co KG
<b>Company Address:</b>	Schillerstraße 5, 78595 Hausen OV, Germany
<b>Company Website:</b>	<a href="http://sikla.com">http://sikla.com</a>
<b>New/Updated Product Listing:</b>	Yes
<b>Listing Country:</b>	Germany
<b>Certification Type:</b>	FM Approved
<b>Class of Work:</b>	1951-Pipe hangers For AS Sys